



DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	20 (Max.)	Kg/Cm
	OPERATING	—	Kg/Cm
TEMP. (SENSOR)	DESIGN	-10 ~ 150°C (180°C OPTION)	
	OPERATING	—	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 60	
	OPERATING	—	
POWER SUPPLY		100~120/200 to 240AC 50/60Hz or 24V DC (OPTION)	
ENCLOSURE		<input type="checkbox"/>	WEATHER PROOF
		<input type="checkbox"/>	EXPLOSION PROOF (Ex d IIC T6,IP65)
RELAY OUTPUT		1SPDT,250V 3A AC,30V 3A DC(RESISTIVE) C-NO : NORMALLY OPEN CONTACT C-NC : NORMALLY CLOSED CONTACT	
DETECTION TIME DELAY		APPROX. 3 to 5 SECONDS FOR COVERED APPROX. 3 to 5 SECONDS FOR FREE	
SENSITIVITY		BULK DENSITY OF 0.2g/cm2 (Min)	
L	<input type="checkbox"/>	250 mm(STD)	
	<input type="checkbox"/>	OPTION ( mm ) Max. 1000mm	
MOUNTING SIZE		JIS 5K 50A FF	
TAG NO.			

NOTES

1. INITIAL RESET TIME : APPROX. 15 SEC.

REVISION

5	CONNECTOR	304SS	1		
4	FLANGE	304SS	1		
3	DETECTION PIPE	304SS	1		
2	COVER	ADC 12	1		
1	HOUSING	ADC 12	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-		
PROJECT	-		
TITLE	VIBRATION TYPE LEVEL SWITCH SVL-15-D-1-A-1-A-1 ASSEMBLY DRAWING		
MANUFACTURER	SeoJin Instech Co., Ltd.		

SCALE		ERP CODE	0000	Work Order No.	-	REV.	
N/S	DWG NO.	SJ-M022-DWG-AP002					

	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED