



WIRING DIAGRAM

△									
△									
△									
△									
△	FOR APPROVAL								
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED				

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	DESIGN 1(Max.) kg/Cm ² OPERATING - kg/Cm ²
TEMP.	DESIGN -10 ~ 90 °C OPERATING - °C
TEMP. (SENSOR)	DESIGN -10 ~ 60 °C OPERATING - °C
CONTACT RATING	-
POWER SUPPLY	15-32V DC(2 WIRE)
ENCLOSURE	EXPLOSION PROOF
OUTPUT	4-20 mA
VISCOSITY	1Pa.s/10P Less
MOISTURE	Max 80%RH

MEASURING RANGE (mm) Max. 20000mm

TAG NO. -

NOTES

REVISION

8	UNION	304SS	1	1 1/2"	
7	TERMINAL BOX ASS'Y	ADC 12	1		
6	TRANSMITTER ASS'Y	ADC 12	1		
5	DRAIN VALVE	MSBE2	1		
4	HOST GEAR ASS'Y	AC2B	1		
3	SCALE COVER	ADC 12	1		
2	BACK COVER	ADC 12	1		
1	INDICATOR BODY	ADC 12	1		

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE	LIQUID TANK LEVEL GAUGE SLT-2200-A-1-A(B)-()-A-2-A ASSEMBLY DRAWING
-------	--

MANUFACTURER

Seoul Instech Co., Ltd.

SCALE

W/S

ISO 9001

0000

Max. Order No. -

REV.

△

DATE

SU-M021-DWG-AP003