



WIRING DIAGRAM

DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	—
PRESS.	DESIGN 1(Max.) kg/cm ² OPERATING — kg/cm ²
TEMP.	DESIGN —10 ~ 90 °C OPERATING — °C
TEMP. (SENSOR)	DESIGN —10 ~ 60 °C OPERATING — °C
CONTACT RATING	250V AC 5A
POWER SUPPLY	15-32V DC(2 WIRE)
ENCLOSURE	EXPLOSION PROOF
OUTPUT	TRANSMITTER 4-20 mA SWITCH 2point 4point
VISCOSITY	1Pa.s/10P Less
MOISTURE	Max 80%RH

MEASURING RANGE (mm) Max. 20000mm

TAG NO. —

NOTES

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
1	INDICATOR BODY	ADC 12	1		
2	BACK COVER	ADC 12	1		
3	SCALE COVER	ADC 12	1		
4	HOST GEAR ASS'Y	AC2B	1		
5	DRAIN VALVE	MSBE2	1		
6	TRANSMITTER ASS'Y	ADC 12	1		
7	TERMINAL BOX ASS'Y	ADC 12	1		
8	UNION	304SS	1	1 1/2"	

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—

TITLE	LIQUID TANK LEVEL GAUGE SLT-4400-B(C)-1-A(B)-()-A-2-A ASSEMBLY DRAWING
-------	---

MANUFACTURER	Seojin Instech Co., Ltd.
SCALE	1000
DATE	0000
REV.	0000
W/S	SJ-MQ21-DWG-AP009