



PA Series

Variable Area Flowmeter

- Field indicated Flow meter for use without power supply
- Designed to fit into small spaces for easy installation in general factory piping lines and panels
- Easily check the flow of fluid (bubble, color, etc.)

PA-70 Series General Specifications

Size	1/4" ~ 1/2"
Process Connection	PT, NPT (Female)
Measured Fluid	Gas and Liquid
Range Ability	10 : 1
Accuracy	±2.0 % F.S
Fluid Temperature	Max. 120 °C

MODEL CODE

PA-20	-	□	-	□	Specification
		2 ~ 6			Piping distribution number
				S	304SS or 316SS
				P	PVC

STANDARD MATERIAL

No.	Description	Material		
		A	B	C
1	Body	BRASS	304SS	PVC
2	Float	304SS	PVC PTFE	316LSS
3	Taper tube	PYREX GLASS		
4	Needle Valve	BRASS	304SS	316SS
5	Packing	NBR, FPM, PTFE		
6	Cover	ACRYL		
7	Mounting shaft bar	BRASS	304SS	316SS
8	Guide bar	304SS	316SS	PTFE LINER

DIMENSIONS

Count \ Type	A	B	C	D
2	36	41	36	41
3	36	23	72	59
4	36	23	108	77
5	36	23	144	95
6	36	23	180	113

STRUCTURAL DRAWING

