



DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	Max. 10	Kg/Cm <sup>2</sup>
	OPERATING	—	Kg/Cm <sup>2</sup>
TEMP. (SENSOR)	DESIGN	−40 ~ 120	°C
	OPERATING	—	°C
TEMP. (ELECTRONICS)	DESIGN	−40 ~ 80	°C
	OPERATING	—	°C
SP.GR.	0.7 ~ 1.3		
ENCLOSURE	WEATHER PROOF		
FLANGE SIZE	ANSI 150# 4" RF		
DISPLACER SIZE	ø76.3x98L		
CONTACT RATING	250V AC 10A		

TAG NO.	L	L1	L2	L3	L4
			—	—	—
			—	—	—
			—	—	—
			—	—	—

NOTES

6	DISPLACER	304SS	1		
5	CHAIN	304SS	1		
4	FLANGE	304SS	1	ANSI 150# 4" RF	
3	STEM	304SS	1		
2	HOUSING	ADC12	1		
1	HOUSING COVER	AC2B	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—			
PROJECT	—			
TITLE	DISPLACEMENT TYPE LEVEL SWITCH SMC-1-A-1-OP-2-A ASSEMBLY DRAWING			
MANUFACTURER	SeoJin Instech Co., Ltd.			
SCALE	1:1	ERP CODE	—	Work Order No. —
REV.	N/A			
DWG NO.	SJ-M013-DWG-AP003			

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED