


3> 2Point (Alarm-SPDT) : HH and LL Alarm



DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID	-		
PRESS.	DESIGN	Max. 30	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP. (SENSOR)	DESIGN	-40 ~ 230	°C
	OPERATING	-	°C
TEMP. (ELECTRONICS)	DESIGN	-40 ~ 80	°C
	OPERATING	-	°C
SP.GR.	0.7 ~ 1.3		
ENCLOSURE	WEATHER PROOF		
FLANGE SIZE	ANSI 150# 4" RF		
DISPLACER SIZE	ø76.3x98L		
CONTACT RATING	250V AC 5A		

TAG NO.	L	L1	L2	L3	L4
				-	-
				-	-
				-	-
				-	-

NOTES

7	COOLING FIN	AL	3		
6	DISPLACER	316SS	2		
5	WIRE	316SS	1		
4	FLANGE	316SS	1	ANSI 150# 4" RF	
3	STEM	316SS	1		
2	HOUSING	ADC12	1		
1	HOUSING COVER	C.S	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
----	-------------	----------	------	---------------	--------

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE	DISPLACEMENT TYPE LEVEL SWITCH SMC-3-B-2-OP-1-A ASSEMBLY DRAWING
-------	--

MANUFACTURER	SeoJin Instech Co., Ltd.
--------------	---------------------------------

SCALE		ERP CODE	-	Work Order No.	-	REV.	
N/S	DWG NO.	SJ-M013-DWG-AP030					

△					
△					
△					
△					
△	FOR APPROVAL	2021.06.14	K.I.CHOI	D.N.LEE	S.H.LEE
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED