



DESIGN DATA					
CODE	N/A				
UNIT	mm				
KIND OF FLUID		-			
PRESS.	DESIGN	Max. 30		Kg/Cm <sup>2</sup>	
	OPERATING	-		Kg/Cm <sup>2</sup>	
TEMP. (SENSOR)	DESIGN	-40 ~ 230		°C	
	OPERATING	-		°C	
TEMP. (ELECTRONICS)	DESIGN	-40 ~ 80		°C	
	OPERATING	-		°C	
SP.GR.		0.7 ~ 1.3			
ENCLOSURE		EXPLOSION PROOF		Ex d IIC T6, IP66	
FLANGE SIZE		ANSI 150# 4" RF			
DISPLACER SIZE		ø76.3x98L			
CONTACT RATING		250V AC 5A			
TAG NO.		L	L1	L2	L3 L4
					- -
					- -
					- -
					- -

NOTES

7	COOLING FIN	AL	3		
6	DISPLACER	316SS	2		
5	WIRE	316SS	1		
4	FLANGE	316SS	1	ANSI 150# 4" RF	
3	STEM	316SS	1		
2	HOUSING	ADC12	1		
1	HOUSING COVER	AC2B	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-				
PROJECT	-				
TITLE	DISPLACEMENT TYPE LEVEL SWITCH SMC-3-B-2-OP-3-A ASSEMBLY DRAWING				
MANUFACTURER	SeoJin Instech Co., Ltd.				
SCALE	1:1	ERP CODE	-	Work Order No.	-
N/S	DWG NO.	SJ-M013-DWG-AP008			REV.

△					
△					
△					
△					
△	FOR APPROVAL				
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED