



DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	ATM
OPERATING	-
DESIGN	-
TEMP. (SENSOR)	-10 ~ 100°C
OPERATING	-
DESIGN	-10 ~ 60
TEMP. (ELECTRONICS)	-
OPERATING	-
POWER SUPPLY	100~120/200 to 240AC 50/60Hz or 24V DC, MAX. 10A
ENCLOSURE	WEATHER PROOF
SP.GR	More than 0.85
L	1000 mm(STD)
MOUNTING SIZE	OPTION (mm) Max. 1500mm
APPLICATION	PT3/4", JIS10K50A
TAG NO.	OPEN & ATM TANK

NOTES

REVISION

7	FLOAT	304SS	1		
6	ROD	304SS	1		
5	STOPPER(SET FREE)	304SS	2		
4	CONNECTOR	304SS	1		
3	BELLOWS	N.B.R	1		
2	CABLE GLAND	MBsBE2	1		
1	BODY	Polyphenol resin	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	UNIFICATION FLOAT TYPE LEVEL SWITCH
	SFS-2S-A-1-A-1
	APPROVAL DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

△					
△					
△					
△	FOR APPROVAL				
△	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

SCALE: N/S

DATE: N/A

REV: N/A

WORK ORDER NO.: 0000

REMARK: S-J-MO07-DWG-AP001