



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID		-
PRESS.	DESIGN	ATM
	OPERATING	-
TEMP.	DESIGN	-10 ~ 100°C
(SENSOR)	OPERATING	-
TEMP.	DESIGN	-10 ~ 60
(ELECTRONICS)	OPERATING	-
POWER SUPPLY		100~120/200 to 240AC 50/60Hz or 24V DC, MAX. 10A
ENCLOSURE		WEATHER PROOF
SP.GR		More than 0.85
L		<input type="checkbox"/> 1000 mm(STD) <input type="checkbox"/> OPTION ( mm ) Max. 1500mm
MOUNTING SIZE		<input type="checkbox"/> PT3/4", <input type="checkbox"/> JIS10K50A
APPLICATION		OPEN & ATM TANK
TAG NO.		

NOTES

SCRW FIXING MOUNTING

REVISION

7	FLOAT	304SS	1	
6	ROD	304SS	1	
5	STOPPER(SET FREE)	304SS	2	
4	CONNECTOR	304SS	1	
3	BELLOWS	N.B.R	1	
2	CABLE GLAND	MBsBE2	1	
1	BODY	Polyphenol resin	1	
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION
				REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	UNIFICATION FLOAT TYPE LEVEL SWITCH SFS-2S-A-1-A-1 APPROVAL DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE	1:1	EXP CODE	0000	Work Order No.	-	REV	1
N/S	DATE NO.	SJ-MO07-DWG-AP001-2					