



DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	-
PRESS.	ATM
OPERATING	-
DESIGN	-
TEMP. (SENSOR)	-10 ~ 100°C
OPERATING	-
DESIGN	-
TEMP. (ELECTRONICS)	-10 ~ 60
OPERATING	-
POWER SUPPLY	100~120/200 to 240AC 50/60Hz or 24V DC, MAX. 10A
ENCLOSURE	WEATHER PROOF
SP.GR	More than 0.85
L	<input type="checkbox"/> 1000 mm(STD) <input type="checkbox"/> OPTION (mm) Max. 1500mm
MOUNTING SIZE	<input type="checkbox"/> PT3/4", <input type="checkbox"/> JIS10K50A
APPLICATION	OPEN & ATM TANK
TAG NO.	

NOTES

REVISION

9	FLANGE	304SS	1		
8	FLOAT	304SS	1		
7	ROD	304SS	1		
6	STOPPER(SET FREE)	304SS	2		
5	CONNECTOR	304SS	1		
4	BELLOWS	N.B.R	1		
3	TIGHT COUPLING	Polyphenol resin	1		
2	CABLE GLAND	MBSBE2	1		
1	BODY	Polyphenol resin	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	UNIFICATION FLOAT TYPE LEVEL SWITCH SFS-2S-A-1-B-1 APPROVAL DRAWING
MANUFACTURER	Seojin Instech Co., Ltd.
SCALE	1:1
DATE	0000
REV.	N/S