



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF MEDIA	-	
PRESS.	DESIGN	ATM
	OPERATING	-
TEMP.	DESIGN	-10 ~ 60 °C
	OPERATING	- °C
ENCLOSURE	WEATHER PROOF	
MOUNTING TYPE&SIZE	PF 3/4"	
POWER SUPPLY	<input type="checkbox"/> AC110V <input type="checkbox"/> AC220V	
POWER CONSUMPTION	1.5VA	
CONTACT CAPACITY	AC250V/3A	
TEMPERATURE	Max. 60°C	
R.P.M	1(50Hz) / 1.2(60Hz)	
TAG NO.	L	

NOTES

REVISION

7	CONNECTOR	304SS	1	
6	PADDLE	PC	1	
5	SHAFT	SUS304	1	
4	CAP	MBSBE2	1	
3	MOUNTING NUT	MBSBE2	1	
2	BODY	ADC12	1	
1	COVER	PC	1	
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION
REMARK				

BILL OF MATERIAL

CUSTOMER	-		
PROJECT	-		
TITLE	PADDLE TYPE LEVEL SWITCH SR7X-1-A-1-A-1-A-2 ASSEMBLY DRAWING		
MANUFACTURER	Seojin Instech Co., Ltd.		
SCALE	1:1	DATE	2024.07.10
REV.	1	REV.	1