



DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF MEDIA		-	
PRESS.	DESIGN	ATM	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP.	DESIGN	-10 ~ 60	°C
	OPERATING	-	°C
ENCLOSURE	WEATHER PROOF		
MOUNTING TYPE&SIZE	JIS 10K 80A FF 6.0t		
POWER SUPPLY	<input type="checkbox"/> AC110V <input type="checkbox"/> AC220V		
POWER CONSUMPTION	1.5VA		
CONTACT CAPACITY	AC250V/3A		
TEMPERATURE	Max. 60°C		
R.P.M	1(50Hz) / 1.2(60Hz)		
TAG NO.	L		

NOTES

REVISION

8	PADDLE	304SS	1	
7	CONNECTOR	304SS	1	
6	SHAFT	304SS	1	
5	CAP	304SS	1	
4	MOUNTING NUT	MBSBE2	1	
3	FLANGE	MBSBE2	1	
2	BODY	ADC12	1	
1	COVER	PC	1	
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION
				REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

TITLE	PADDLE TYPE LEVEL SWITCH SR7X-1-A-1-A-1-C-2 ASSEMBLY DRAWING
-------	--

△					
△					
△					
△	APPROVAL				
△	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE: N/A

DATE NO. SU-MO27-DWG-AP004

REV. 1