

DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF MEDIA	—		
PRESS.	DESIGN OPERATING	ATM —	Kg/Cm^2 Kg/Cm^2
TEMP.	DESIGN OPERATING	$-10 \sim 60$ —	$^{\circ}\text{C}$ $^{\circ}\text{C}$
ENCLOSURE MOUNTING TYPE&SIZE	WEATHER PROOF PF 1"		
POWER SUPPLY	<input type="checkbox"/> AC110V <input type="checkbox"/> AC220V		
POWER CONSUMPTION	1.5VA		
CONTACT CAPACITY	AC250V/3A		
TEMPERATURE	Max. 60°C		
R.P.M	1(50Hz) / 1.2(60Hz)		

R.P.M	1(50Hz) / 1.2(60Hz)
-------	---------------------

R.P.M	1(50Hz) / 1.2(60Hz)
-------	---------------------

R.P.M	1(50Hz) / 1.2(60Hz)
-------	---------------------

R.P.M	1(50Hz) / 1.2(60Hz)
-------	---------------------

R.P.M	1(50Hz) / 1.2(60Hz)
-------	---------------------

R.P.M	1(50Hz) / 1.2(60Hz)
-------	---------------------

NOTES

REVISION

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
6	PADDLE	304SS	1		
5	SHAFT	304SS	1		
4	STEM PIPE	MS36B2	1		
3	UNION COUPLER	MS36B2	1		
2	BODY	ADCI2	1		
1	COVER	PC	1		

BILL OF MATERIAL

CUSTOMER

PROJECT



TITLE	
-------	--

PADDLE TYPE LEVEL SWITCH
SR7X-1-B-1-A-3-B-1
ASSEMBLY DRAWING

MANUFACTURER

SeoJin Instech Co., Ltd.

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△	APPROVAL	2018.01.29			

SCALE			EXP CODE	Work Order No.	REV.
N/A			-	-	0
DWG NO:	SU-M027-DWG-AP005				