

DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF MEDIA		-	
PRESS.	DESIGN	ATM	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP.	DESIGN	-10 ~ 60	°C
	OPERATING	-	°C

ENCLOSURE	WEATHER PROOF
MOUNTING TYPE&SIZE	PT 1"
POWER SUPPLY	<input type="checkbox"/> AC110V <input type="checkbox"/> AC220V
POWER CONSUMPTION	1.5VA
CONTACT CAPACITY	AC250V/5A
TEMPERATURE	Max. 60°C
R.P.M	1(50Hz) / 1.2(60Hz)


TAG NO.	L

NOTES

REVISION

7	PADDLE	304SS	1		
6	CONNECTOR	304SS	1		
5	SHAFT	304SS	1		
4	STEM PIPE	MBSBE2	1		
3	UNION COUPLER	MBSBE2	1		
2	BODY	ADC12	1		
1	COVER	PC	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

CUSTOMER	—
PROJECT	—

TITLE						PADDLE TYPE LEVEL SWITCH SR7X-1-B-1-A-3-B-2 ASSEMBLY DRAWING			
MANUFACTURER									
Seojin Instech Co., Ltd.									
△						SCALE			
△						N/A			
△						<div><div><div></div><div>TIME NO.</div></div><div><div>SJ-M027-DWG-AP006</div><div>0</div></div></div> <div><div><div>EXP. CODE</div><div>-</div></div><div><div>Work Order No.</div><div>-</div></div></div> <div><div>REV.</div><div>0</div></div>			
△	APPROVAL	2018.01.29							