



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF MEDIA		-
PRESS.	DESIGN	ATM
	OPERATING	-
TEMP.	DESIGN	-10 ~ 60 °C
	OPERATING	- °C
ENCLOSURE	WEATHER PROOF	
MOUNTING TYPE&SIZE	JIS 10K 80A FF 6.0t	
POWER SUPPLY	<input type="checkbox"/> AC110V <input type="checkbox"/> AC220V	
POWER CONSUMPTION	1.5VA	
CONTACT CAPACITY	AC250V/3A	
TEMPERATURE	Max. 60°C	
R.P.M	1(50Hz) / 1.2(60Hz)	
TAG NO.	L	

NOTES

REVISION

7	PADDLE	304SS	1	
6	SHAFT	304SS	1	
5	STEM PIPE	304SS	1	
4	CONNECTION PIPE	304SS	1	
3	UNION COUPLER	304SS	1	
2	BODY	ADC12	1	
1	COVER	PC	1	
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION
				REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	PADDLE TYPE LEVEL SWITCH SR7X-1-B-1-A-3-C-1 ASSEMBLY DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE	1:1	DATE	2018.01.29	DESIGNED		REVIEWED		APPROVED	
REV.	1	DESCRIPTION	APPROVAL						