

CH-8000L

2 Motor



FEATURE

- Height Adjustable, Longopac / Plastic Bag Available and Advanced Technology.
- Auto Filter Cleaning System (patented)
- PTFE HEPA Filter (fine dust collection up to 0.3μ)
- Wide Application
 - Surface Preparation Service (concrete grinding/polishing/scarifying)
 - Construction Site, Factory and Warehouse

CH-9000L

3 Motor



Specification	CH-8000L	CH-9000L
Voltage	220V 50/60Hz	220V 50/60Hz
Power	2400W(3.2HP)	3600W(4.7HP)
Air Pressure	2600mmAq	3000mmAq
Tank Capacity	Longopac/Plastic Bag	Longopac/Plastic Bag
Hose	ID 45Ø/50Ø	ID 45Ø/50Ø
Motor Type	Dry/Wet	Dry/Wet
Noise	65db	75db
Dimension (LxWxH)	70x60x140cm	78x65x152cm
Weight	62kg (net)	75kg (net)

CH-9000S (with Cyclone Separator)

FEATURE

- 95~97% collected dust drops into the separator, it allows not only to collect large amount dust, but to last filter & motors.
- Wide Application
 - Concrete Grinding/Polishing/Scarifying
 - Construction Site, factory and warehouse

