

BENDS

series
ELF

Protection	Gas	Zone	1-2	II2G	Ex d IIC Gb / Ex e IIC Gb
	Dusts	21-22	II2D		Ex tb IIC Db

Degree of Protection	IP66/67
----------------------	---------

Amb. Temp.	Standard	-55°C	+150°C
	Extended	-60°C	+180°C




Entries Threading	NPT ANSI B1.20 or Metric ISO 262
-------------------	----------------------------------

Material	Aluminium
----------	-----------


Standards and Certificates	Directive 2014/34/EU (ATEX) EN 60079 - 0 • EN 60079 - 1 EN 60079 - 7 • EN 60079 - 31 CE CESA 01 ATEX 104U IEC 60079 - 0 • IEC 60079 - 1 IEC 60079 - 7 • IEC 60079 - 31 IEC-Ex CES 15.0005U
----------------------------	---

- 90° Bends Series ELF are used in the electrical installation in tube.

Options - Size greater than 3".



Code	Dimensions (mm)				Weight (g)
	ØA	L	H	R	
ELF 1	1/2" NPT	60	45	30	120
ELF 2	3/4" NPT	75	55	30	100
ELF 3	1" NPT	85	65	35	200
ELF 4	1.1/4" NPT	100	75	50	390
ELF 5	1.1/2" NPT	110	87	50	370
ELF 6	2" NPT	135	98	60	620
ELF 7	2.1/2" NPT	175	135	65	880
ELF 8	3" NPT	210	160	85	1480



Code	Dimensions (mm)				Weight (g)
	ØA	L	H	R	
ELF 20	M20x1.5	60	45	30	120
ELF 25	M25x1.5	75	55	30	100
ELF 32	M32x1.5	85	65	35	200
ELF 40	M40x1.5	100	75	50	390
ELF 50	M50x1.5	110	87	50	370
ELF 63	M63x1.5	135	98	60	620
ELF 75	M75x1.5	175	135	65	880
ELF 90	M90x1.5	210	160	85	1480

Example: ELF3

Order Coding

Type
ELF

Size and Threading

1/2/3/4/5/6/7/8 = NPT ANSI B1.20
20/25/32/40/50/63/75/80/85/90 = Metric ISO 262

Material

- = Aluminum