

Round Type Current Transformer (1.15kV)



- 옥내용 (For Indoor)
- 1차 Cable or Bus-bar 관통형
(For Cable or Bus-bar Through Type)
- 일반 계기 및 보호 계전기용 (For Metering & Protection)
- Epoxy Mold
- 2차 단자 커버

Specification

Service	Type	Current Ratio (A)	Accuracy Class (%)	Burden (VA)	n>	Hole size (mm)	Weight (kg)
Metering	RL616	100 ~ 2000 / 5	1.0	5	—	65	≒13
		100 ~ 2000 / 5		15	—		
		200 ~ 2000 / 5		30	—		
		250 ~ 2000 / 5		40	—		
		250 ~ 2000 / 5		40	—		
Protection	RL616R	100 ~ 2000 / 5	5P	5	10		
		100 ~ 2000 / 5		5	20		
		100 ~ 2000 / 5		15	10		
		300 ~ 2000 / 5		15	20		
		250 ~ 2000 / 5		30	10		
		400 ~ 2000 / 5		40	10		
Metering	RL616	100 ~ 2000 / 1	1.0	5	—		
		100 ~ 2000 / 1		15	—		
		150 ~ 2000 / 1		30	—		
		200 ~ 2000 / 1		40	—		
Protection	RL616R	100 ~ 2000 / 1	5P	5	10		
		100 ~ 2000 / 1		5	20		
		100 ~ 2000 / 1		15	10		
		400 ~ 2000 / 1		15	20		
		400 ~ 2000 / 1		30	10		
		500 ~ 2000 / 1		40	10		

※ Application Standard : KS C 1706, IEC 61869-2, JEC 1201, IEEE C 57.13, etc.

※ Insulation Level : 1.15 kV / 4 kV / -

※ Rated Frequency : 60 Hz (Others on request)

※ Short time current : 40 In / 1 second (Others on request)

※ 주문사양에 따라 Accuracy Class는 0.3, 0.5 Class등 다양하게 제작이 가능합니다.

※ 이중비, 2core CT의 생산이 가능하므로 주문시 협의 바랍니다.

Dimension & Drawing

