



DESIGN DATA	
CODE	N/A
UNIT	mm
KIND OF FLUID	—
LIFE TIME OF BELLOWS	100,000 TIMES
LIFE TIME OF CONTACT	500,000 TIMES
INSULATION RESISTANCE	OVER 100Ω AC250V
MAX. PRESSURE	10kg/Cm ² (1000KPa)
TEMPERATURE	Max 80°C
MOISTURE	Max 80% RH
OUTPUT CONTACT CAPACITY	AC 120V 5A / AC 240V 5A

NOTES

REVISION

6	PADDLE	304SS	1		
5	SHAFT	MBsBE2	1		
4	SOCKET	MBsBE2	1		
3	TERMINAL BOX BASE	SS41	1		
2	CABLE GLAND PACKING	NBR	1		
1	TERMINAL BOX COVER	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—
TITLE	PADDLE TYPE FLOW SWITCH SF-3-A-1-A APPROVAL DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

△					
△					
△					
△	FOR APPROVAL				
△	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED

SCALE	DATE	REV	SCALE	DATE	REV
N/S	SJ-M006-DWG-AP001	0000	N/S	SJ-M006-DWG-AP001	0000