



△						
△						
△						
△						
△						
REV.	DESCRIPTION	DATE	DESIGNED	CHECKED	REVIEWED	APPROVED

DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	Max. 10	Kg/Cm <sup>2</sup>
	OPERATING	—	Kg/Cm <sup>2</sup>
TEMP. (SENSOR)	DESIGN	−10 ~ 100	°C
	OPERATING	—	°C
CABLE STRENGTH	Max. 2		Kg/Cm <sup>2</sup>
LEAD WIRE LENGTH	300 mm		
SP.GR.	0.8		
ENCLOSURE	N/A		
MOUNTING SIZE ("A")	<input type="checkbox"/> PF 1/4"	<input type="checkbox"/> PF 1/8"	
FLOAT SIZE	ø25x25L		
MAX. OPER. VOLTAGE	AC300V, DC300V		
MAX. OPER. CURRENT	AC0.5A, DC0.5A		
MAX. CONTACT CAPACITY	AC50VA, DC50W		

NOTES

5	STOPPER	P.P	1		
4	FLOAT	P.P	1		
3	BODY	P.P	1		
2	MOUNTING NUT	P.P	1		
1	LEAD WIRE	—	1		
NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—				
PROJECT	—				
TITLE	MINI FLOAT TYPE LEVEL SWITCH SOL-2P ASSEMBLY DRAWING				
MANUFACTURER	<b>SeoJin Instech Co., Ltd.</b>				
SCALE	N/S	ERP CODE	—	Work Order No.	—
DWG NO.	SJ-M002-DWG-AP004				