

VIEW "A"

△						
△						
△						
△						
△						
REV.	DESCRIPTION	DATE	DESIGNED	CHECKED	REVIEWED	APPROVED

DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID	—		
PRESS.	DESIGN	Max. 10	Kg/Cm ²
	OPERATING	—	Kg/Cm ²
TEMP. (SENSOR)	DESIGN	−10 ~ 100	°C
	OPERATING	—	°C
CABLE STRENGTH	Max. 2 Kg/Cm ²		
LEAD WIRE LENGTH	300 mm		
SP.GR.	0.8		
ENCLOSURE	N/A		
MOUNTING SIZE	PF 1/4"		
FLOAT SIZE	25x25L		
MAX. OPER. VOLTAGE	AC300V, DC300V		
MAX. OPER. CURRENT	AC0.5A, DC0.5A		
MAX. CONTACT CAPACITY	AC50VA, DC50W		

NOTES

5	STOPPER	P.P	1	Polypropylene	
4	FLOAT	P.P	1	Pyrene Foam	
3	BODY	P.P	1	Polypropylene	
2	MOUNTING NUT	P.P	1	Polypropylene	
1	LEAD WIRE	—	1		

NO	DESCRIPTION	MATERIAL	Q'TY	SPECIFICATION	REMARK
----	-------------	----------	------	---------------	--------



BILL OF MATERIAL

CUSTOMER	—
----------	---

PROJECT	—
---------	---

TITLE	MINI FLOAT TYPE LEVEL SWITCH SOLH-3 ASSEMBLY DRAWING
-------	--

MANUFACTURER	 SeoJin Instech Co., Ltd.
--------------	---

SCALE		ERP CODE	—	Work Order No.	—	REV.	
N/S	DWG NO.	SJ-M002-DWG-AP005					