



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	—	
PRESS.	DESIGN	Max. 2 Kg/Cm ²
	OPERATING	— Kg/Cm ²
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	-
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	- °C
SP.GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
FLANGE SIZE	JIS 10K 100A FF	
FLAT TYPE	ø80x110L (STD.)	
S/W CAPACITY	AC250V 3A, AC125V 5A	
WEIGHT MAT'L(OPTION)	304SS 316SS (ø60x80)	
CONTACT TYPE	A 점 접 B 점 접 A&B 점 접 SPT(2-WIRE) SPD(3-WIRE)	
TAG NO.	L	L1 L2 L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	1	MERCURY	
4	CABLE	0.18SQx2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—				
PROJECT	—				
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQC-1-A-1-A-1-A-1 ASSEMBLY DRAWING				
MANUFACTURER	Seojin Instech Co., Ltd.				
SCALE	1:1	EXP CODE	—	Work Order No.	—
DATE	N/S	SU-M004-DWG-AP025	REV		