

DESIGN DATA				
CODE	N/A			
UNIT	mm			
KIND OF FLUID		-		
PRESS.	DESIGN OPERATING	Max. 2 -	Kg/Cm ² Kg/Cm ²	
TEMP. (SENSOR)	DESIGN OPERATING	-10 ~ 70 -	°C °C	
TEMP. (ELECTRONICS)	DESIGN OPERATING	-10 ~ 70 -	°C °C	
SP. GR.		MORE THAN 0.9		
VISCOSITY		10 P / 1 Pas		
ENCLOSURE	WEATHER PROOF			
FLANGE SIZE		JIS 10K 100A FF		
FLAT TYPE		ø80x110L (STD.)		
S/W CAPACITY		AC250V 3A, AC125V 5A		
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS	(ø60x80)		
CONTACT TYPE	<input type="checkbox"/> A 點接 <input type="checkbox"/> B 點接	<input type="checkbox"/> A&B 點接		
	SPST(2-WIRE)	SPDT(3-WIRE)		
TAG NO.	L	L1	L2	L3




NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	2	MERCURY	
4	CABLE	0.1850x2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-		
PRODUCT	-		
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQC-2-A-1-A-1-A-1 ASSEMBLY DRAWING		
MANUFACTURER	 SeoJin Instech Co., Ltd.		
SCALE	 DWG. NO.	EXP. CODE	WORK ORDER NO.
N/S	SU-M004-DWG-AP026	-	-
	 REV.		