

DESIGN DATA				
CODE	N/A			
UNIT	mm			
KIND OF FLUID		-		
PRESS.	DESIGN OPERATING	Max. 2 -	Kg/Cm ² Kg/Cm ²	
TEMP.	DESIGN	-10 ~ 70	°C	
TEMP. (SENSOR)	OPERATING	-	°C	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 70	°C	
	OPERATING	-	°C	
SP.GR.		MORE THAN 0.9		
VISCOSITY		10 P / 1 Pas		
ENCLOSURE		WEATHER PROOF		
FLANGE SIZE		JIS 10K 100A FF		
FLOAT TYPE		ø80x110L (STD.)		
S/W CAPACITY		AC250V 3A, AC125V 5A		
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS	(ø60x80)		
CONTACT TYPE	<input type="checkbox"/> A 접점 <input type="checkbox"/> B 접점 <input type="checkbox"/> A&B 접점	SPDT(2-WIRE) SPDT(3-WIRE)		
TAG NO.	L	L1	L2	L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	3	MERCURY	
4	CABLE	0.1850x2	—		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER

PROJECT

TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH
-------	--------------------------------------


SQC-3-A-1-A-1-A-1

ASSEMBLY DRAWING

MANUFACTURER



Seojin Instech Co., Ltd.

SCALE			REV.
	DWG. NO.	TBP CODE Work Order No.	
N/S	SJ-M004-DWG-AP027		