



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	-	
PRESS.	DESIGN	Max. 2 Kg/Cm ²
	OPERATING	- Kg/Cm ²
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	- °C
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	- °C
SP.GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
FLANGE SIZE	JIS 10K 100A FF	
FLANGE TYPE	ø80x110L (STD.)	
S/W CAPACITY	AC250V 3A, AC125V 5A	
WEIGHT MAT(L(OPTION))	304SS □ 316SS (ø60x80)	
CONTACT TYPE	□ A 점접 □ B 점접 □ A&B 점접	
	SPST(2-WIRE) SPDT(3-WIRE)	
TAG NO.	L	L1 L2 L3 L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	4	MERCURY	
4	CABLE	0.18SQx2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH
	SQC-4-A-1-A-1-A-1
	ASSEMBLY DRAWING

Seojin Instech Co., Ltd.

SCALE	1:1	REV	1
DATE	2024.04.10	REV	1
NO.	SJ-M004-DWG-AP028	REV	1