



DESIGN DATA									
CODE	N/A								
UNIT	mm								
KIND OF FLUID	-								
	DESIGN	Max. 2 Kg./Cm ²							
PRESS.	OPERATING	- Kg./Cm ²							
TEMP.	DESIGN	-10 ~ 70 °C							
	OPERATING	- °C							
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 70 °C							
	OPERATING	- °C							
SP.GR.	MORE THAN 0.9								
	10 P / 1 Pa.s								
VISCOSITY	WEATHER PROOF								
ENCLOSURE	JIS 10K 100A FF								
FLANGE SIZE	ø80x110L (STD.)								
FLANGE TYPE	AC250V 3A, AC125V 5A								
S/W CAPACITY	<input type="checkbox"/> 30ASS	<input type="checkbox"/> 316SS	(ø60x80)						
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> A 常閉	<input type="checkbox"/> B 常開	<input type="checkbox"/> A&B 常閉						
	SPST(2-WIRE)		SPDT(3-WIRE)						
CONTACT TYPE									
TAG NO.	L	L1	L2	L3	L4				

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	4	MERCURY	
4	CABLE	0.18SQx2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQC-4-A-2-A-1-A-1 ASSEMBLY DRAWING

MANUFACTURER

 **Seojin Instech Co., Ltd.**

SCALE

 N/S

DATE NO.

REV. CODE

WORK ORDER NO.

REV.

SU-M004-DWG-AP030

