



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	-	
PRESS.	DESIGN OPERATING	Max. 2 Kg/Cm ²
TEMP.	DESIGN OPERATING	-10 ~ 70 °C
TEMP. (SENSOR)	DESIGN OPERATING	-10 ~ 70 °C
TEMP. (ELECTRONICS)	DESIGN OPERATING	-10 ~ 70 °C
SP. GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pas	
ENCLOSURE	WEATHER PROOF	
FLANGE SIZE	JIS 10K 100A FF	
FLANGE DIMENSION	OD ϕ "A" BCD ϕ "B"	N H. t
FLANGE TYPE	ϕ 210 ϕ 175 8 ϕ 19 18	
S/W CAPACITY	AC250V 3A, AC125V 5A	
WEIGHT MAT(L(OPTION))	304SS <input type="checkbox"/> 316SS <input type="checkbox"/> (60x80)	
CONTACT TYPE	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> A&B <input type="checkbox"/> SPDT(2-WIRE) <input type="checkbox"/> SPDT(3-WIRE)	
TAG NO.	L L1 L2 L3 L4 L5	

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	5	MERCURY	
4	CABLE	0.18SQx2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQC-5-A-1-A-1-A-1 ASSEMBLY DRAWING

Seolin Instech Co., Ltd.

SCALE	1:1	REV	1
DATE	2024.04.04	REV	1
REV	1	REV	1