



DESIGN DATA									
CODE	N/A								
UNIT	mm								
KIND OF FLUID	DESIGN	-							
	OPERATING	-							
PRESS.	DESIGN	Max. 2		Kg/Cm <sup>2</sup>					
TEMP.	DESIGN	-10 ~ 70		°C					
TEMP.	OPERATING	-		°C					
TEMP.	DESIGN	-10 ~ 70		°C					
(ELECTRONICS)	OPERATING	-		°C					
SP.GR.	MORE THAN 0.9								
VISCOSITY	10 P / 1 Pa.s								
ENCLOSURE	WEATHER PROOF								
FLANGE SIZE	JIS 10K 100A FF								
FLANGE DIMENSION	O.D. φ"A"		B.C.D. φ"B"	N	H	t			
	φ210		φ175	8	φ19	18			
FLANGE TYPE	φ67x120L (STD.)								
S/W CAPACITY	AC120V 1A								
WEIGHT MAT.(OPTION)	<input type="checkbox"/> 304SS		<input type="checkbox"/> 316SS		(φ60x80)				
CONTACT TYPE	<input type="checkbox"/> A 접점		<input type="checkbox"/> B 접점		공통점				
	SPST(2-WIRE)		SPDT(2-WIRE)		SPDT(4-WIRE)				
TAG NO.	L	L1	L2	L3					

NOTES

1. ( ) Dimensions are reference dimensions.

REVISION

7	WEIGHT	304SS	1	
6	ROPE	304SS	1	
5	FLOAT	316SS	1	
4	CABLE	0.185Qx2	-	
3	EYE-BOLT(M8)	C.S	1	
2	FLANGE	304SS	1	
1	TERMINAL BOX	ABS	1	

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
BILL OF MATERIAL					
CUSTOMER					
PROJECT					

TITLE QUICK FLOAT HOLDER TYPE LEVEL SWITCH  
SQE-T-A-T-B-T-A-T  
ASSEMBLY DRAWING

MANUFACTURER  
**Seojin Instech Co., Ltd.**

SCALE	DATE	REV.
N/S	SJ-M004-DWG-AP031	