



DESIGN DATA									
CODE	N/A								
UNIT	mm								
COND. OF FLUID	—								
PRESS.	DESIGN OPERATING	Max. 2	Kg/Cm ²						
TEMP.	DESIGN OPERATING	—	Kg/Cm ²						
(SENSOR)	DESIGN OPERATING	—10 ~ 70	°C						
TEMP.	DESIGN OPERATING	—10 ~ 70	°C						
(ELECTRONICS)	OPERATING	—	°C						
SP. GR.	MORE THAN 0.9								
VISCOSITY	10 P / 1 Pcs								
ENCLOSURE	WEATHER PROOF								
FLANGE SIZE	JIS 10K 100A FF								
FLANGE DIMENSION	0.D ϕ 7" A B C D ϕ 8" T	N	H	t					
	ϕ 210	ϕ 175	8	ϕ 19	18				
FLAT TYPE	ϕ 67x120L (STD.)								
S/W CAPACITY	AC120V 1A								
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS	<input type="checkbox"/> 316SS	(60x80)						
CONTACT TYPE	<input type="checkbox"/> A 点触	<input type="checkbox"/> B 点触	ϕ 6.8- ϕ 8						
	SPST(2-WIRE)		SPDT(2-WIRE)						
TAG NO.	L	L1	L2	L3					

NOTES

1. () Dimensions are reference dimensions.

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
7	WEIGHT	304SS	1		
6	ROPE	304SS	1		
5	FLOAT	316SS	3		
4	CABLE	0.1850x2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	304SS	1		
1	TERMINAL BOX	ABS	1		

BILL OF MATERIAL

CUSTOMER

PROJECT

TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQE-3-A-1-B-1-A-1 ASSEMBLY DRAWING
-------	---

MANUFACTURER



Seojin Instech Co., Ltd.

SCALE			REV.
N/S	EPR CODE -	Work Order No. -	
DWG. NO.	SU-M004-DWG-AP033		