



DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	—
PRESS.	Max. 2 Kg/Cm ²
OPERATING	— Kg/Cm ²
TEMP.	—10 ~ 70 °C
DESIGN	— °C
TEMP.	—10 ~ 70 °C
DESIGN	— °C
(ELECTRONICS)	— °C
SP.GR.	MORE THAN 0.9
VISCOSITY	10 P / 1 Pa.s
ENCLOSURE	WEATHER PROOF
FLANGE SIZE	JIS 10K 100A FF
FLANGE DIMENSION	OD φ"A" BCD φ"B" N H. t φ210 φ175 8 φ19 18
FLANGE TYPE	φ67x120L (STD.)
S/W CAPACITY	AC120V 1A
WEIGHT MAT(L(OPTION))	304SS □ 316SS (φ60x80)
CONTACT TYPE	□ A 1P1 □ B 1P1 (SPST(2-WIRE))
TAG NO.	L L1 L2 L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	304SS	1	
6	ROPE	304SS	1	
5	FLOAT	316SS	4	
4	CABLE	0.185Qx2	—	
3	EYE-BOLT(M8)	C.S	1	
2	FLANGE	304SS	1	
1	TERMINAL BOX	ABS	1	
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION
				REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQE-4-A-1-B-1-A-1 ASSEMBLY DRAWING

Seojin Instech Co., Ltd.

SCALE	1:1	REV	1
DATE	SU-M004-DWG-AP03.4	REV	1