



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	—	
PRESS.	DESIGN	Max. 2 Kg/Cm ²
	OPERATING	— Kg/Cm ²
TEMP.	DESIGN	—10 ~ 70 °C
	OPERATING	— °C
TEMP.	DESIGN	—10 ~ 70 °C
	OPERATING	— °C
SP.GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
FLANGE SIZE	JIS 10K 100A FF	
FLANGE DIMENSION	O.D. φA" B.C.D. φB"	N H. t
	φ210 φ175 8 φ19 18	
FLOAT TYPE	φ67x120L (STD.)	
S/W CAPACITY	AC120V 1A	
WEIGHT MAT.(OPTION)	304SS	316SS (φ60x80)
CONTACT TYPE	A B C D E F G H I J K L M N O P Q R S T U V W X Y Z	
TAG NO.	L	L1 L2 L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	304SS	1	
6	ROPE	304SS	1	
5	FLOAT	316SS	4	
4	CABLE	0.1850x2	—	
3	EYE-BOLT(M8)	C.S	1	
2	FLANGE	304SS	1	
1	TERMINAL BOX	ABS	1	

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQE-4-A-2-B-1-A-1 ASSEMBLY DRAWING

Seojin Instech Co., Ltd.

SCALE	DATE	REV.
N/S	SU-M004-DWG-AP036	