



DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	-		
PRESS.	DESIGN	Max. 2	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP.	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
TEMP.	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
SP.GR.	MORE THAN 0.9		
VISCOSITY	10 P / 1 Pa.s		
ENCLOSURE	WEATHER PROOF		
FLANGE SIZE	JIS 10K 100A FF		
FLANG TYPE	ø80x110L (STD.)		
S/W CAPACITY	AC250V 3A, AC125V 5A		
WEIGHT MAT(L(OPTION))	30A5S □ 316SS □ (ø60x80)		
CONTACT TYPE	□ A 점접 □ B 점접 □ A&B 점접		
	SPST(2-WIRE) SPDT(3-WIRE)		
TAG NO.	L	L1	L2 L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	1		
4	CABLE	0.185Qx2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQH-1-A-1-B-1-A-1 ASSEMBLY DRAWING

MANUFACTURER	Seojin Instech Co., Ltd.
SCALE	N/S
DATE	SU-M004-DWG-AP007
REV.	
DESCRIPTION	
DATE	
DESIGNED	
REVIEWED	
APPROVED	