



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	-	
PRESS.	DESIGN	Max. 2 Kg/Cm <sup>2</sup>
	OPERATING	- Kg/Cm <sup>2</sup>
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	- °C
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	- °C
SP.GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
MOUNTING SIZE	PF 2"	
FLOAT TYPE	ø80x110L (STD.)	
S/W CAPACITY	AC250V 3A, AC125V 5A	
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS (ø60x80)	
CONTACT TYPE	<input type="checkbox"/> A 점 접 <input type="checkbox"/> B 점 접 <input type="checkbox"/> A&B 점 접	
	SPT(2-WIRE)	SPDT(3-WIRE)
TAG NO.	L	L1 L2

NOTES

1. ( ) Dimensions are reference dimensions.

REVISION

6	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	2		
3	CABLE	0.18SQx2	-		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQH-2-A-1-A-1-A-1 ASSEMBLY DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE	DATE	REV
N/S	SJ-M004-DWG-AP002	