



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID		
PRESS.	DESIGN OPERATING	Max. 2 Kg/Cm <sup>2</sup>
TEMP.	DESIGN OPERATING	-10 ~ 70 °C
TEMP. (ELECTRONICS)	DESIGN OPERATING	-10 ~ 70 °C
SP.GR.		MORE THAN 0.9
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
FLANGE SIZE	JIS 10K 100A FF	
FLANGE TYPE	ø80x110L (STD.)	
S/W CAPACITY	AC250V 3A, AC125V 5A	
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS (ø60x80)	
CONTACT TYPE	<input type="checkbox"/> A 점 접 <input type="checkbox"/> B 점 접 <input type="checkbox"/> A&B 점 접	
	SPT(2-WIRE) SPT(3-WIRE)	
TAG NO.	L L1 L2	

NOTES

1. ( ) Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	2		
4	CABLE	0.18SQx2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQH-2-A-1-B-1-A-1 ASSEMBLY DRAWING
MANUFACTURER	Seojin Instech Co., Ltd.
SCALE	N/S
DATE	SU-M004-DWG-AP008
REV.	