



DESIGN DATA				
CODE	N/A			
UNIT	mm			
KIND OF FLUID		-		
PRESS.	DESIGN OPERATING	Max. 2	Kg/Cm ²	
TEMP.	DESIGN OPERATING	-	Kg/Cm ²	
TEMP. (SENSOR)	OPERATING	-10 ~ 70	°C	
TEMP. (ELECTRONICS)	DESIGN OPERATING	-10 ~ 70	°C	
SP.GR.		-	°C	
VISCOSITY		MORE THAN 0.9		
ENCLOSURE		10 P / 1 Pas		
WEATHER PROOF				
FLANGE SIZE	JIS 10K 100A FF			
FLOAT TYPE	ø80x110L (STD.)			
S/W CAPACITY	AC250V 3A, AC125V 5A			
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS (ø60x80)			
CONTACT TYPE	<input type="checkbox"/> A 接点 <input type="checkbox"/> B 接点 <input type="checkbox"/> A&B 接点 SPST(2-WIRE) SPDT(3-WIRE)			
TAG NO.	L	L1	L2	L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
7	WEIGHT	PVC CASE	1	C.S+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	3		
4	CABLE	0.1850x2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDP	1		
1	TERMINAL BOX	ABS	1		

BILL OF MATERIAL

CUSTOMER

PROJECT

TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH
-------	--------------------------------------

ASSEMBLY DRAWING

MANUFACTURER



Seojin Instech Co., Ltd.

SCALE			ERP CODE	-	Work Order No.	-	REV.	
N/S	DWG NO.		SU-M004-DWG-AP009					

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△					