



△									
△									
△									
△									
REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED				

DESIGN DATA

CODE	N/A		
UNIT	mm		
KIND OF FLUID		Max. 2	Kg/Cm ²
PRESS.	DESIGN OPERATING	-	Kg/Cm ²
TEMP.	DESIGN OPERATING	-10 ~ 70	°C
TEMP.	DESIGN OPERATING	-10 ~ 70	°C
TEMP.	DESIGN OPERATING	-	°C
SP.GR.		MORE THAN 0.9	
VISCOSITY	10 P / 1 Pa.s		
ENCLOSURE	WEATHER PROOF		
MOUNTING SIZE	PF 2"		
FLOAT TYPE	ø80x110L (STD.)		
S/W CAPACITY	AC250V 3A, AC125V 5A		
WEIGHT MAT'L(OPTION)	304SS 316SS (ø60x80)		
CONTACT TYPE	A 점접 B 점접 SPT(2-WIRE) SPT(3-WIRE)		
TAG NO.	L L1 L2 L3 L4		

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	4		
3	CABLE	0.18SQx2	-		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQH-4-A-1-A-1-A-1 ASSEMBLY DRAWING

MANUFACTURER

 **Seojin Instech Co., Ltd.**

SCALE

N/S

DATE NO.

SU-MO04-DWG-AP004

REV.

△