

DESIGN DATA				
CODE	N/A			
UNIT	mm			
KIND OF FLUID		-		
PRESS.	DESIGN OPERATING	Max. 2 -	Kg/Cm ² Kg/Cm ²	
TEMP. (SENSOR)	DESIGN OPERATING	-10 ~ 70 -	°C °C	
TEMP. (ELECTRONICS)	DESIGN OPERATING	-10 ~ 70 -	°C °C	
SP.GR.		MORE THAN 0.9		
VISCOSITY		10 P / 1 Pa.s		
ENCLOSURE	WEATHER PROOF			
FLANGE SIZE	JIS 10K 100A FF			
FLOAT TYPE	ø80x110L (STD.)			
S/W CAPACITY	AC250V 3A, AC125V 5A			
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS (ø60x80)			
CONTACT TYPE	<input type="checkbox"/> A 1점 <input type="checkbox"/> B 2점 <input type="checkbox"/> A&B 3점 SPST(2-WIRE) SPDT(3-WIRE)			
TAG NO.	L	L1	L2	L3
				L4

NOTES






1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S+PVC CASED	STD
6	ROPE	NYLON			
5	FLOAT	ABS	4		
4	CABLE	0.1850x2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—

TITLE		
QUICK FLOAT [®] HOLDER TYPE LEVEL SWITCH		
S&H-4-A-1-B-1-A-1		
ASSEMBLY DRAWING		
MANUFACTURER		
 Seodin Instech Co., Ltd.		
SCALE		
N/S		
DWG. NO.		
	ISO CODE	WORK ORDER NO.
	-	-
SJ-M004-DWG-AP010		REV.
		