



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	—	
PRESS.	DESIGN	Max. 2 Kg/Cm ²
	OPERATING	— Kg/Cm ²
TEMP.	DESIGN	−10 ~ 70 °C
	OPERATING	— °C
TEMP.	DESIGN	−10 ~ 70 °C
	OPERATING	— °C
SP.GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
MOUNTING SIZE	PF 2"	
FLOAT TYPE	ø80x110L (STD.)	
S/W CAPACITY	AC250V 3A, AC125V 5A	
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS (ø60x80)	
CONTACT TYPE	<input type="checkbox"/> A 常閉 <input type="checkbox"/> B 常開 <input type="checkbox"/> A&B 常閉常開	
	<input type="checkbox"/> SPST(2-WIRE) <input type="checkbox"/> SPDT(3-WIRE)	
TAG NO.	L	L1 L2 L3 L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	4		
3	CABLE	0.18SQx2	—		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQH-4-A-2-A-1-A-1 ASSEMBLY DRAWING

MANUFACTURER

Seojin Instech Co., Ltd.

SCALE	DATE	REV.
N/S	SJ-M004-DWG-AP006	