

DESIGN DATA				
CODE	N/A			
UNIT	mm			
KIND OF FLUID	-			
PRESS.	DESIGN OPERATING	Max. 2 -	Kg/Cm ² Kg/Cm ²	
TEMP.	DESIGN	-10 ~ 70	°C	
TEMP. (SENSOR)	OPERATING	-	°C	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 70	°C	
	OPERATING	-	°C	
SP.GR.		MORE THAN 0.9		
VISCOSITY		10 P / 1 Pas		
ENCLOSURE	WEATHER PROOF			
FLANGE SIZE	JIS 10K 100A FF			
FLOAT TYPE	ø80x110L (STD.)			
S/W CAPACITY	AC250V 3A, AC125V 5A			
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS (ø60x80)			
CONTACT TYPE	<input type="checkbox"/> A 접점 <input type="checkbox"/> B 접점 <input type="checkbox"/> A&B 접점 SPST(2-WIRE) SPDT(3-WIRE)			
TAG NO.	L	L1	L2	L3
				L4

NOTES

1. () Dimensions are reference dimensions.

REVISION


7	WEIGHT	PVC CASE	1	C.S.+PVC CASSED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	4		
4	CABLE	0.1850x2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—

TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQH-4-A-2-B-1-A-1 ASSEMBLY DRAWING
-------	---

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVE
△					
△					
△					
△					
△					

SCALE			REV.
	DWG. NO.	REV.	
N/S			
	SJ-M004-DWG-AP012		