



DESIGN DATA

CODE	N/A
UNIT	mm
KIND OF FLUID	—
PRESS.	Max. 2 Kg/Cm ²
OPERATING	— Kg/Cm ²
TEMP. (SENSOR)	—10 ~ 70 °C
OPERATING	— °C
TEMP. (ELECTRONICS)	—10 ~ 70 °C
OPERATING	— °C
SP.GR.	MORE THAN 0.9
VISCOSITY	10 P / 1 Pa.s
ENCLOSURE	WEATHER PROOF
MOUNTING SIZE	PF 2"
FLOAT TYPE	ø80x110L (STD.)
S/W CAPACITY	AC250V 3A, AC125V 5A
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS <input type="checkbox"/> (ø60x80)
CONTACT TYPE	<input type="checkbox"/> A 점 접 <input type="checkbox"/> B 점 접 <input type="checkbox"/> A&B 점 접
	SPT(2-WIRE) SPT(3-WIRE)
TAG NO.	L L1 L2 L3 L4 L5

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	5		
3	CABLE	0.18SQx2	—		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQH-5-A-1-A-1-A-1 ASSEMBLY DRAWING

MANUFACTURER
Seojin Instech Co., Ltd.

SCALE	1:1	REV. CODE	—	Work Order No.	—	REV.	1
DATE	2024.04.05	SU-M004-DWG-AP005					