

DESIGN DATA					
CODE	N/A				
UNIT	mm				
KIND OF FLUID		-			
PRESS.	DESIGN OPERATING	Max. 2	Kg/Cm ²		
(SENSOR)	DESIGN	-	Kg/Cm ²		
	OPERATING	-10 ~ 70	°C		
TEMP.	DESIGN	-	°C		
	OPERATING	-10 ~ 70	°C		
(ELECTRONICS)	OPERATING	-	°C		
SP. GR.	MORE THAN 0.9				
VISCOSITY	10 P / 1 Pas				
ENCLOSURE	WEATHER PROOF				
FLANGE SIZE	JIS 10K 100A FF				
FLAT TYPE	ø80x110L (STD.)				
S/W CAPACITY	AC250V 3A, AC125V 5A				
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS	(ø60x80)			
CONTACT TYPE	<input type="checkbox"/> A 挿針 <input type="checkbox"/> B 挿針	<input type="checkbox"/> A&B 挿針			
	SPST(2-WIRE)	SPDT(3-WIRE)			
TAG NO.	L	L1	L2	L3	L4

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	5		
4	CABLE	0.1850x2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL


CUSTOMER

PROJECT

TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH
-------	--------------------------------------


307-3-A-1-B-1-A-1
ASSEMBLY DRAWING

MANUFACTURER



Seojin Instech Co., Ltd.

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△					

<p>SCALE</p> <p>N/S</p>			
	<p>EXP. CODE</p> <p>-</p>	<p>WORK ORDER NO.</p> <p>-</p>	<p>REV.</p> <p>0</p>
<p>DWG. NO.</p> <p>SJ-M004-DWG-AP011</p>			
<p>MANUFACTURER</p> <p>SeoJin Instech Co., Ltd.</p>			