

DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	DESIGN	-	
	OPERATING	-	
PRESS.	DESIGN	Max. 2	Kg/Cm <sup>2</sup>
	OPERATING	-	Kg/Cm <sup>2</sup>
TEMP. (SENSOR)	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
SP.GR.	MORE THAN 0.9		
VISCOSITY	10 P / 1 Pa.s		
ENCLOSURE	WEATHER PROOF		
MOUNTING SIZE	PF 2"		
FLOAT TYPE	ø50×68L (STD.)		
S/W CAPACITY	AC/DC 250V / 0.2A		
WEIGHT MAT(L(OPTION))	<input type="checkbox"/> 304SS	<input type="checkbox"/> 316SS	(ø60×80)
CONTACT TYPE	<input type="checkbox"/> A 점접	<input type="checkbox"/> B 점접	SPST(2-WIRE) <del>SPST(2-WIRE) 100mA/125V</del>
TAG NO.	L	L1	L2
	L3		

NOTES

1. ( ) Dimensions are reference dimensions.


REVISION

6	WEIGHT	PVC CASE	1	C.S.+PVC CASD	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	1		
3	CABLE	0.18SQx2	-		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK


BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQM-1-A-1-A-1-A-1 ASSEMBLY DRAWING

MANUFACTER

 **Seojin Instech Co., Ltd.**


SCALE

 N/S

DATE NO.

SU-M004-DWG-AP013

REV



APP CODE

-

WORK ORDER NO.

-