



DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	DESIGN	-	
	OPERATING	-	
PRESS.	DESIGN	Max. 2	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP. (SENSOR)	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
SP.GR.	MORE THAN 0.9		
VISCOSITY	10 P / 1 Pa.s		
ENCLOSURE	WEATHER PROOF		
FLANGE SIZE	JIS 10K 100A FF		
FLANGE TYPE	ø50x68L (STD.)		
S/W CAPACITY	AC/DC 250V / 0.2A		
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS	<input type="checkbox"/> 316SS	(ø60x80)
CONTACT TYPE	<input type="checkbox"/> A 접점	<input type="checkbox"/> B 접점	SPST(2-WIRE) (STD)
TAG NO.	L	L1	L2
	L1	L2	L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	1		
4	CABLE	0.18SQx2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-				
PROJECT	-				
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SOM-1-A-1-B-1-A-1 ASSEMBLY DRAWING				
MANUFACTURER	Seojin Instech Co., Ltd.				
SCALE		EXP CODE	Work Order No.	REV	
N/S	DATE NO.	SU-M004-DWG-AP019			