



DESIGN DATA			
CODE	N/A		
UNIT	mm		
KIND OF FLUID	-		
PRESS.	DESIGN	Max. 2	Kg/Cm ²
	OPERATING	-	Kg/Cm ²
TEMP.	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
TEMP.	DESIGN	-10 ~ 70	°C
	OPERATING	-	°C
SP.GR.	MORE THAN 0.9		
VISCOSITY	10 P / 1 Pa.s		
ENCLOSURE	WEATHER PROOF		
MOUNTING SIZE	PF 2"		
FLOAT TYPE	ø50×68L (STD.)		
S/W CAPACITY	AC/DC 250V / 0.2A		
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS	<input type="checkbox"/> 316SS	(ø60x80)
CONTACT TYPE	<input type="checkbox"/> A 점점	<input type="checkbox"/> B 점점	SPST(2-WIRE) SPST(2-WIRE) 100% 100%
TAG NO.	L	L1	L2

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	2		
3	CABLE	0.18SQx2	-		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-		
PROJECT	-		
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQM-2-A-1-A-1-A-1 ASSEMBLY DRAWING		
MANUFACTURER	Seojin Instech Co., Ltd.		
SCALE	1:1	EXP CODE	Work Order No.
DATE	N/S	SU-M004-DWG-AP014	REV