

DESIGN DATA				
CODE	N/A			
UNIT	mm			
COND. OF FLUID	-			
PRESS.	DESIGN	Max. 2	Kg/Cm <sup>2</sup>	
TEMP.	OPERATING	-	Kg/Cm <sup>2</sup>	
TEMP. (SENSOR)	DESIGN	-10 ~ 70	°C	
TEMP.	OPERATING	-	°C	
(ELECTRONICS)	DESIGN	-10 ~ 70	°C	
SP. GR.	OPERATING	-	°C	
VISCOSITY	MORE THAN 0.9			
ENCLOSURE	10 P / 1 Pcs			
WEATHER PROOF	PF 2"			
MOUNTING SIZE	ø50x86L (STD.)			
F/OUT TYPE	AC/DC 250V / 0.2A			
S/W CAPACITY	304SS □ 316SS (ø60x80)			
WEIGHT MATL(OPTION)	□ A 鋁合金	□ B 鋁合金	SPIN-ON WIRE	
CONTACT TYPE	SPIN-ON WIRE			
TAG NO.	L	L1	L2	L3


## REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
6	WEIGHT	PVC CASE	1	CS+PVC CASED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	3		
3	CABLE	0.1850x2	-		
2	EYE-BOLT(M8)	C/S	1		
1	TERMINAL BOX	ABS	1		

## BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△					

MANUFACTURER			
SeoJin Instech Co., Ltd.			
SCALE	N/S		
	EXP. CODE	Work Order No.	REV.
DWG. NO.	S/J-M004--DWG-APD15		