

DESIGN DATA				
CODE	N/A			
UNIT	mm			
COND. OF FLUID	-			
PRESS.	DESIGN OPERATING	Max. 2 -	Kg./Cm <sup>2</sup> Kg./Cm <sup>2</sup>	
TEMP.	DESIGN	-10 ~ 70	°C	
TEMP. (SENSOR)	OPERATING	-	°C	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 70	°C	
	OPERATING	-	°C	
SP. GR.	MORE THAN 0.9			
VISCOSITY	10 P / 1 Pcs			
ENCLOSURE	WEATHER PROOF			
MOUNTING SIZE	PF 2"			
FLOAT TYPE	ø50x68L (STD.)			
S/W CAPACITY	AC/DC 250V / 0.2A			
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS	(ø60x80)		
CONTACT TYPE	<input type="checkbox"/> A 短型 <input type="checkbox"/> B 短型			
	SPST(2-WIRE)	SPST(2-WIRE) <del>SPST(2-WIRE)</del>		
TAG NO.	L	L1	L2	L3

## NOTES







1. ( ) Dimensions are reference dimensions.

## REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
6	WEIGHT	PVC CASE	1	C.S+PVC CASSED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	4		
3	CABLE	0.1850x2	-		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		

## BILL OF MATERIAL

CUSTOMER	-
PROJECT	-

MANUFACTURER			
 <b>SeoJin Instech Co., Ltd.</b>			
SCALE			
N/S			
	DWG. NO.	EIP CODE	WORK ORDER NO.
	SJ-M004-DWG-AP016	-	-
			
	REV.		