



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	—	
PRESS.	DESIGN	Max. 2 Kg/Cm ²
	OPERATING	— Kg/Cm ²
TEMP.	DESIGN	—10 ~ 70 °C
	OPERATING	— °C
TEMP.	DESIGN	—10 ~ 70 °C
	OPERATING	— °C
SP.GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pa.s	
ENCLOSURE	WEATHER PROOF	
FLANGE SIZE	JIS 10K 100A FF	
FLANGE TYPE	ø50x68L (STD.)	
S/W CAPACITY	AC/DC 250V / 0.2A	
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS	<input type="checkbox"/> 316SS (ø60x80)
CONTACT TYPE	<input type="checkbox"/> A 형(1) <input type="checkbox"/> B 형(1)	<input type="checkbox"/> C 형(1) <input type="checkbox"/> D 형(1)
	SPST(2-WIRE) SPST(2-WIRE) SPST(2-WIRE) SPST(2-WIRE)	
TAG NO.	L	L1 L2 L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

7	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	4		
4	CABLE	0.18SQx2	—		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	—
PROJECT	—
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SOM-4-A-1-B-1-A-1 ASSEMBLY DRAWING

MANUFACTURER

Seolin Instech Co., Ltd.

SCALE: N/S

DATE: N/A

REV: N/A

DESCRIPTION: N/A

DATE: N/A

DESIGNED: N/A

REVIEWED: N/A

APPROVED: N/A