

DESIGN DATA				
CODE	N/A			
UNIT	mm			
KIND OF FLUID	-			
PRESS.	DESIGN OPERATING	Max. 2 -	Kg/Cm ² Kg/Cm ²	
TEMP.	DESIGN	-10 ~ 70	°C	
TEMP. (SENSOR)	OPERATING	-	°C	
TEMP. (ELECTRONICS)	DESIGN	-10 ~ 70	°C	
	OPERATING	-	°C	
SP.GR.	MORE THAN 0.9			
VISCOSITY	10 P / 1 Pas			
ENCLOSURE	WEATHER PROOF			
MOUNTING SIZE	PF 2"			
FLOAT TYPE	φ50x68L (STD.)			
S/W CAPACITY	AC/DC 250V / 0.2A			
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS	<input type="checkbox"/> 316SS	(φ60x80)	
CONTACT TYPE	<input type="checkbox"/> A 접점	<input type="checkbox"/> B 접점	1000-518	
	SPST(2-WIRE)		SHD-6-200	
TAG NO.	L	L1	L2	L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
6	WEIGHT	PVC CASE	1	C.S+PVC CASSED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	4		
3	CABLE	0.18SQ2	—		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		

BILL OF MATERIAL

CUSTOMER

CUSTOMER

PROJECT

PROJECT

title	quick float holder type level switch
-------	--------------------------------------

SQM-4-A-2-A-1-A-1



ASSEMBLY DRAWING

MANUFACTURER



Seojin Instech Co., Ltd.

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVED
△					
△					
△					
△					
△					

MANUFACTURER			
 SeoJin Instech Co., Ltd.			
SCALE N/S			
DWG. NO. S-J-M004-DWG-AP018	 EXP. CODE -	WORK ORDER NO. -	REV. 