

DESIGN DATA				
CODE	N/A			
UNIT	mm			
COND. OF FLUID		-		
PRESS.	DESIGN	Max. 2	Kg/Cm ²	
	OPERATING	-	Kg/Cm ²	
TEMP.	DESIGN	-10 ~ 70	°C	
(SENSOR)	OPERATING	-	°C	
TEMP.	DESIGN	-10 ~ 70	°C	
(ELECTRONICS)	OPERATING	-	°C	
SP. GR.		MORE THAN 0.9		
VISCOSITY		10 P / 1 Pas		
ENCLOSURE	WEATHER PROOF			
FLANGE SIZE	JIS 10K 100A FF			
FLOAT TYPE	φ50xφ8L (STD.)			
S/W CAPACITY	AC/DC 250V / 0.2A			
WEIGHT MAT'L(OPTION)	<input type="checkbox"/> 304SS <input type="checkbox"/> 316SS	(φ60x80)		
CONTACT TYPE	<input type="checkbox"/> A 접점 <input type="checkbox"/> B 접점	100% SIL		
	SPST(2-WIRE)	SHD(4-WIRE)		
TAG NO.	L	L1	L2	L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK
7	WEIGHT	PVC CASE	1	C.S.+PVC CASSED	STD
6	ROPE	NYLON	1		
5	FLOAT	ABS	4		
4	CABLE	0.1850x2	-		
3	EYE-BOLT(M8)	C.S	1		
2	FLANGE	HDPE	1		
1	TERMINAL BOX	ABS	1		

BILL OF MATERIAL

CUSTOMER

PROJECT



TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQM-4-A-2-B-1-A-1 ASSEMBLY DRAWING
-------	-------------------------------------------------------------------------------

MANUFACTURER



Seojin Instech Co., Ltd.

REV.	DESCRIPTION	DATE	DESIGNED	REVIEWED	APPROVE
△					
△					
△					
△					
△					

<p>MANUFACTURER</p> <p>SeoJin Instech Co., Ltd.</p>			
<p>MODEL</p> <p>SQM-4-A-2-B-1-A-1</p> <p>ASSEMBLY DRAWING</p>			
<p>SCALE</p> <p>N/S</p>			
		<p>EXP. CODE</p> <p>-</p>	<p>WORK ORDER NO.</p> <p>-</p>
<p>DWG. NO.</p> <p>SJ-M004-DWG-AP024</p>		<p>REV.</p> <p>0</p>	