



DESIGN DATA

CODE	N/A	
UNIT	mm	
KIND OF FLUID	-	
PRESS.	DESIGN	Max. 2 Kg/Cm ²
	OPERATING	- Kg/Cm ²
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	- °C
TEMP.	DESIGN	-10 ~ 70 °C
	OPERATING	- °C
SP.GR.	MORE THAN 0.9	
VISCOSITY	10 P / 1 Pas	
ENCLOSURE	WEATHER PROOF	
MOUNTING SIZE	PF 2"	
FLOAT TYPE	ø50x68L (STD.)	
S/W CAPACITY	AC/DC 250V / 0.2A	
WEIGHT MAT(L(OPTION))	304SS □ 316SS (ø60x80)	
CONTACT TYPE	□ A 접점 □ B 접점 (SPST(2-WIRE) SPST(2-WIRE) (SPST(2-WIRE))	
TAG NO.	L	L1 L2 L3

NOTES

1. () Dimensions are reference dimensions.

REVISION

6	WEIGHT	PVC CASE	1	C.S.+PVC CASED	STD
5	ROPE	NYLON	1		
4	FLOAT	ABS	5		
3	CABLE	0.18SQx2	-		
2	EYE-BOLT(M8)	C.S	1		
1	TERMINAL BOX	ABS	1		
NO	DESCRIPTION	MATERIAL	QTY	SPECIFICATION	REMARK

BILL OF MATERIAL

CUSTOMER	-
PROJECT	-
TITLE	QUICK FLOAT HOLDER TYPE LEVEL SWITCH SQM-5-A-1-A-1-A-1 ASSEMBLY DRAWING

Seojin Instech Co., Ltd.

SCALE	1:1	REV	1
DATE	2024.04.17	REV	1
REV	1	REV	1